International Journal of Web of Multidisciplinary Studies
(Peer-Reviewed, Open Access, Fully Refereed International Journal)
website: *https://ijwos.com*
Volume 03, Issue 11,November 2026
OPEN ACCESS
E-ISSN : 3049-2424
DOI: https://doi.org/10.71366/ijwos

Real-Time Driver Drowsiness Detection System Using OpenCV, Facial Landmark Tracking, and Machine Learning

Tumpala Teja[1], Yadagiri Kanaka Mahalakshmi[2], Siyyadri Padmapriya[3], B. Ganesh[4]
[1], [2], [3]Master of Computer Applications Final Year Students, Department of Computer Science & Engineering, Avanthi Institute of Engineering & Technology, Anakapalli, Andhra Pradesh, India
[4]Associate Professor, Department of Computer Science & Engineering, Avanthi Institute of Engineering & Technology, Anakapalli, Andhra Pradesh, India

Article Info

Article History:
Published: 04 Nov 2026

Publication Issue:
Volume 03, Issue 11
November 2026

Page Number:
32-36

Corresponding Author:
Tumpala Teja

Abstract:
Driver drowsiness is a critical contributor to global traffic accidents, necessitating the development of non-intrusive, real-time monitoring solutions to ensure road safety. This paper presents a cost-effective, real-time drowsiness detection system that leverages computer vision and machine learning algorithms to continuously monitor a driver's facial features and mitigate fatigue-related hazards. Utilizing a standard 720p dashboard webcam, the system captures live video feeds and maps 68 facial landmarks using dlib and OpenCV. The core detection mechanism relies on computing the Eye Aspect Ratio (EAR) across consecutive frames to track eye closure duration. For enhanced verification and robustness, a TensorFlow-based Convolutional Neural Network (CNN) is integrated alongside MediaPipe Face Mesh. Additionally, a localized Flask web application provides a real-time analytics dashboard built with HTML, JavaScript, and Tailwind CSS to track telemetry and driver alertness statistics. Experimental validation confirms that the system accurately differentiates between physiological micro-blinks and sustained fatigue closures, successfully triggering an audible emergency alert within 2.0 seconds of drowsiness onset. The framework demonstrates high resilience across challenging environmental conditions, including low-light illumination and subjects wearing corrective spectacles, delivering a dependable, lightweight edge-safety solution.

Keywords: Drowsiness detection, OpenCV, Machine Learning, Eye Aspect Ratio (EAR), Driver fatigue, Convolutional Neural Network (CNN), dlib 68-landmarks, Road safety.

1. Introduction

Driver drowsiness is recognized internationally as one of the leading causative factors in catastrophic vehicular crashes. With exponential growth in commercial freight transit, passenger haulage, and extended highway transit durations, driver exhaustion substantially impairs cognitive responsiveness, prolongs physiological reaction times, and degrades hazard assessment skills. Traditional preventative measures have relied on driver self-regulation, which frequently fails due to circadian micro-sleep episodes occurring without conscious awareness.

Prior automated drowsiness detection research falls predominantly into three paradigms: physiological measurement systems (e.g., electroencephalography [EEG], electrocardiography [ECG]), vehicular behavior analytics (e.g., steering wheel deviations, lane trajectory drifting), and visual computer vision systems. While physiological sensors provide direct neuro-physical data, they require cumbersome, intrusive physical electrodes that cause physical discomfort and distract drivers. Similarly, vehicle-based metric systems require extended temporal accumulation before anomalous steering patterns can be confirmed, rendering them slow and susceptible to variable road conditions. Consequently, real-time vision-based telemetry utilizing non-intrusive dashboard cameras has emerged as the most practical, cost-effective, and driver-acceptable paradigm.

Copyright © 2026 The Author(s) : This is an open access article under the CC BY license (http://creativecommons.org/licenses/by-nc/4.0/)

To address these operational constraints, this paper details the engineering and empirical validation of an end-to-end, lightweight drowsiness detection framework. Operating on consumer-grade hardware without requiring specialized graphical processing accelerators, the system captures real-time video, tracks 68 anatomical facial landmarks, dynamically calculates the Eye Aspect Ratio (EAR), cross-verifies anomalous eye states using a lightweight Convolutional Neural Network (CNN), and enforces an automated audio siren interrupt when eye closure duration exceeds a validated 2.0-second safety threshold.

2. LITERATURE REVIEW

Computer vision methodologies for driver fatigue tracking have evolved substantially over the past two decades. Viola and Jones (2004) established the benchmark for rapid real-time facial localization through boosted Haar cascade classifiers. Soukupova and Cech (2016) revolutionized non-intrusive eye fatigue monitoring by formulating the Eye Aspect Ratio (EAR), demonstrating that facial landmark coordinates provide scale-invariant geometric measurements of eye opening without expensive feature training.

Recent implementations have extended these foundational principles. M. B. N (2016) proposed automated facial monitoring targeting eye and mouth regions for sleep-related traffic accident mitigation [1]. Alshaqaqi et al. (2013) demonstrated vision-based monitoring utilizing continuous frame image processing [2]. Baek et al. (2018) focused on optimizing real-time embedded algorithms for automotive Driver State Monitoring Systems (DSMS) using low-power infrared optics [3]. You et al. (2019) addressed the challenge of physical variation among individual drivers, formulating adaptive thresholds to account for physiological disparities in natural eye geometry [4].

In consumer-grade embedded deployments, Malathesha et al. (2025) formulated 'Driver Guard', demonstrating that lightweight machine learning on webcam streams runs efficiently on consumer CPUs without high-end GPU clusters [5]. Thampi et al. (2026) developed a hybrid framework leveraging MediaPipe Face Mesh and OpenCV to track fatigue markers [6]. Baul et al. (2025) validated real-time mesh coordinates for fatigue mitigation [7], while Madhusudhanam and Kumar (2026) analyzed hardware overhead constraints in low-cost vehicle architectures [8]. To improve robustness against poor image resolution and visual noise, Venkateswarlu and Ch (2024) designed DrowsyDetectNet, a compact CNN architecture capable of generalizing on limited training partitions [9]. Abd El-Nabi et al. (2025) deployed advanced image denoising and transformer pipelines to improve nighttime facial feature integrity [10].

3. PROPOSED METHODOLOGY AND WORKFLOW

The proposed driver state monitoring architecture is designed as a decoupled, multi-stage processing pipeline optimized for deterministic execution on CPU-only hardware. The overall architectural topology and procedural workflow are illustrated in Fig. 1.



Fig. 1. End-to-end drowsiness detection architecture, procedural execution pipeline, and multi-modal alerting workflow.

A. Step-by-Step Computational Workflow

The operational lifecycle of continuous video frames passing through the inspection pipeline adheres to five synchronized stages:

1) Real-Time Video Ingestion: Live telemetric video is captured via a dashboard-facing standard 720p webcam at 30 frames per second (FPS). Inbound frames are downscaled and preprocessed using OpenCV (grayscale conversion and contrast enhancement).

2) Facial Boundary Detection: The dlib frontal face detector (or MediaPipe Face Mesh) parses the frame to establish the primary region of interest (ROI) bounding the driver's face.

3) 68-Point Anatomical Landmark Mapping: A pre-trained facial landmark predictor maps 68 distinct structural points across the face. Points 37–42 isolate the right eye perimeter, and points 43–48 isolate the left eye perimeter.

4) Eye Aspect Ratio (EAR) Computation: Euclidean distances between vertical eyelid landmarks are divided by the horizontal ocular width to generate instantaneous EAR values for both eyes, as detailed in Section IV.

5) Threshold Verification & Alert Triggering: Computed EAR is compared against the calibrated fatigue threshold (EAR_thresh = 0.20). If EAR remains below 0.20 for 48 consecutive frames (spanning 2.0 seconds at ~24–30 FPS), an emergency audio alarm sounds, and telemetry logs push alerts to the Flask dashboard.

4. MATHEMATICAL FORMULATION & ALGORITHMIC ARCHITECTURE

The geometric foundation governing eye state evaluation is the Eye Aspect Ratio (EAR). For a given eye represented by six 2D coordinate pairs (P1 through P6), the ratio is formulated as:

$$EAR = (||p2 - p6|| + ||p3 - p5||) / (2 \cdot ||p1 - p4||) \quad (1)$$

where ||p_i - p_j|| represents the standard 2D Euclidean distance between landmark points:

$$||p_i - p_j|| = \sqrt{ ((x_i - x_j)^2 + (y_i - y_j)^2)} \quad (2)$$

The numerator reflects vertical eyelid aperture, whereas the denominator characterizes horizontal eye length. Because the horizontal distance remains relatively invariant during blinks, EAR drops rapidly toward zero when eyelids shut, providing an illumination- and distance-invariant metric. To account for asymmetrical ocular closures, the composite score is averaged:

$$EAR_{avg} = (EAR_{left} + EAR_{right}) / 2 \quad (3)$$

A. Landmark Spatial Configuration & Temporal Profile

Fig. 2 illustrates the anatomical positioning of the 6-point ocular polygon alongside the dynamic temporal response curve distinguishing normal physiological blinks (duration < 350 ms) from sustained drowsy episodes (> 2.0 seconds).



Fig. 2. (Left) 6-point eye landmark arrangement (P1–P6); (Right) Temporal EAR response curve displaying rapid blink recovery vs. sustained drowsiness threshold violation.

B. Secondary CNN Classification Layer

To eliminate potential false alarms induced by head orientation variations, smiling, or partial occlusion, an auxiliary lightweight Convolutional Neural Network (CNN) built in TensorFlow is invoked whenever EAR fluctuates near the

decision boundary ($0.19 \leq EAR \leq 0.22$). The CNN takes cropped 32x32 eye image patches and predicts binary eye state probability P(Closed), reinforcing decision confidence before alarm triggering.

5. EXPERIMENTAL RESULTS AND PERFORMANCE ANALYSIS

The experimental framework was evaluated under real-time conditions using an Intel Core i3 CPU (2.4 GHz) with 8 GB RAM and a standard 720p USB webcam operating at 30 FPS. Testing partitions encompassed multiple subjects across four realistic environmental scenarios: nominal daytime lighting, dim low-light ambient conditions, subjects wearing corrective spectacles, and varying facial pitch/yaw angles.

A. Scenario-Based Validation Matrix

Table I summarizes the empirical performance metrics across distinct operational environments. In all conditions, the system effectively preserved low false-alarm frequencies while triggering emergency sirens within the 2.0-second SLA.

Operational Testing Scenario	Observed EAR (Closed)	Detection Latency (s)	Classification Accuracy (%)	Alert Reliability
Normal Lighting (Clear Eyes)	**0.11 ± 0.02**	**1.65 s**	**98.2%**	**100% (No False Negatives)**
Low-Light / Night Driving	0.13 ± 0.03	1.82 s	95.4%	97.5% (Robust Contrast)
Corrective Spectacles / Glasses	0.14 ± 0.03	1.88 s	94.8%	96.0% (Stable Landmarks)
Off-Center Yaw/Pitch Angles	0.15 ± 0.04	1.95 s	93.1%	94.5% (CNN Supported)

TABLE I. Real-Time Drowsiness Detection Performance Across Operational Scenarios

B. Algorithmic Benchmark Comparison

To establish comparative efficacy, Table II outlines performance against alternative fatigue detection approaches documented in literature. The proposed hybrid EAR + CNN pipeline achieves optimal equilibrium between high inference accuracy (96.8% overall) and sub-35ms frame processing overhead.

Detection Methodology	Hardware Requirement	Frame Latency (ms)	Overall Accuracy (%)
Haar Cascades + Template Matching	Standard CPU	22 ms	84.5%
Heavyweight 3D ResNet CNN	Dedicated GPU (NVIDIA)	68 ms	97.2%
Proposed Dlib EAR + Compact CNN	**Standard CPU (No GPU)**	**28 ms**	**96.8%**

TABLE II. Comparative Architectural Benchmark of Drowsiness Detection Pipelines

C. Web Analytics Dashboard Deployment

The integrated Flask dashboard serves as an interactive telemetry console. Operating with an asynchronous WebSocket pipeline, the interface displays live video overlays, streaming EAR plots, real-time blink frequency counters, and fatigue severity status. The responsive UI built with Tailwind CSS ensures seamless rendering across mobile driver terminals and fleet management monitors.

6. CONCLUSION AND FUTURE SCOPE

This research presented the design, implementation, and empirical validation of an affordable, non-intrusive driver drowsiness detection system. By fusing dlib 68-point facial landmark geometry with dynamic Eye Aspect Ratio calculation and secondary CNN classification, the framework achieves 96.8% detection accuracy without requiring dedicated GPU acceleration. The system reliably discriminates between benign physiological blinks and hazardous micro-sleep occurrences, reliably activating an audible emergency alert within 2.0 seconds. Empirical benchmarks across low-light driving scenarios and spectacle-wearing drivers confirm high operational resilience.

Future enhancements will incorporate multi-modal fatigue biomarkers—specifically yawning frequency via Mouth Aspect Ratio (MAR) and head posture tracking (yaw, pitch, roll) via 3D Perspective-n-Point (PnP) pose estimation. Additionally, lightweight edge deployment on embedded systems (e.g., Raspberry Pi 5 or NVIDIA Jetson Nano) paired with automotive CAN-bus telematics will allow automated vehicle deceleration in critical micro-sleep emergencies.

References

[1] M. B. N, "Facial features monitoring for real time drowsiness detection," in Proc. 2016 12th Int. Conf. Innovations Inf. Technol. (IIT), 2016, pp. 1–5.

[2] A. S. Alshaqaqi et al., "Driver drowsiness detection system," in Proc. 2013 8th Int. Workshop Syst., Signal Process. Their Appl. (WoSSPA), 2013, pp. 151–155.

[3] J. W. Baek et al., "Real Time Drowsiness Detection Algorithm for Driver State Monitoring Systems," in Proc. 2018 10th Int. Conf. Ubiquitous Future Netw. (ICUFN), 2018, pp. 883–885.

[4] F. You et al., "A Real-time Driving Drowsiness Detection Algorithm with Individual Differences Consideration," IEEE Access, vol. 7, pp. 179396–179408, 2019.

[5] N. Malathesha, M. V. Kash, P. T. Reddy, and N. C. Aditya, "Driver Drowsiness Detection Using OpenCV and Machine Learning," Int. J. Eng. Dev. Res. (IJEDR), vol. 13, no. 4, pp. 721–725, 2025.

[6] L. L. Thampi, C. T. Neethu, and M. A. Aswathy, "Smart Driver Assistance: Real-Time Drowsiness Detection Leveraging Facial Cues with MediaPipe and OpenCV," Int. J. Intell. Transp. Syst. Res., 2026.

[7] S. Baul, M. R. Rana, N. J. Trisna, and F. B. Alam, "Development of a Real-time Driver's Drowsiness Detection System Using MediaPipe Face Mesh," Int. J. Eng. Manuf. (IJEM), vol. 15, no. 5, pp. 46–57, 2025.

[8] M. R. Madhusudhanam and K. H. M. Kumar, "A Camera-Based Driver Drowsiness Detection System Using OpenCV," Int. J. Eng. Dev. Res. (IJEDR), vol. 14, no. 1, pp. 908–917, 2026.

[9] M. Venkateswarlu and V. R. R. Ch, "DrowsyDetectNet: Driver Drowsiness Detection Using Lightweight CNN With Limited Training Data," IEEE Access, vol. 12, pp. 110476–110491, 2024.

[10] S. Abd El-Nabi et al., "Driver Drowsiness Detection Using Swin Transformer and Diffusion Models for Robust Image Denoising," IEEE Access, vol. 13, pp. 71880–71907, 2025.